



VICENZA Cinque Terre




VOLO Stone Mountain




Parco Querini




Scamozzi




Doeskin




Flint




Salvi




Costozza




American Gothic




Coffee Bean




Etna



Villa Saraceno




Thundercloud




Marine Blue



Torreguaceto




Lumignano




Laurel




Deep Olive




Palazzo Chiericati



Black




Garnet



Black

Technical Information

Width/ Pattern	Fabric Grade	Fiber Content & Backing	Weight	Protective Finish	Abrasion Resistance	Light- fastness	Approx. Repeats	Cl. Code
50–55 Sq. Ft. Vicenza    	L2	Corrected grain, aniline dyed, heavily finished leather	2.25–2.50 oz./ Sq. Ft.	Breathable Protective Finish	ASTM D7255 1,000+ Cycles (CS-10 Wheels)	AATCC Method 16, Option E, 72 Hours Class 4	N/A	MSW
50–55 Sq. Ft. Volo    	L2	Corrected grain, aniline dyed, heavily finished leather	2.50–2.75 oz./ Sq. Ft.	Breathable Protective Finish	ASTM D7255 1,000+ Cycles (CS-10 Wheels)	AATCC Method 16, Option E, 72 Hours Class 4	N/A	MSW

EXPLANATION OF ACT ICONS FOR UPHOLSTERY

Fire Retardancy

Flammability testing determined as fabric's resistance to burning.

PASSES California 117

Colorfastness to Wet and Dry Crocking

Colorfastness to wet & dry crocking refers to the rubbing off of color from the fabric onto clothing, hands or other materials and can occur under wet or dry conditions.

PASSES ASTM D5053 Dry: Class 4–5, Wet: Class 4

Colorfastness to Light

Colorfastness to light is the degree to which fabric will retain its color when exposed to light.

PASSES AATCC Method 16, Option E, 72 Hours: Class 4

Physical Properties

3 physical property tests include: brush pill test to determine a fabric's pilling. Breaking/tensile strength is the ability of a fabric to withstand tension without breaking or tearing. Seam slippage is the pulling apart of fabrics at the seams.

PASSES Breaking Strength ASTM D2208 150 lb.

Abrasion

Abrasion is the ability of a fabric to withstand damage from wear and rubbing. There is a general contract specification as well as heavy duty specification.

PASSES
(General Contract) ASTM D7255
1,000+ Cycles (CS-10 Wheels)

Cleaning Code Definitions

MSW Dust regularly. Minor spots can be washed off using lukewarm water and mild soap. Do not soak. Never clean with abrasive solvents, alcohol or wax-based products.

Please visit manufacturer's website for cleaning instructions at www.spinneybeck.com

TORONTO

5800 Avebury Road, Unit 2
Mississauga, ON L5R 3M3

SKU BF9841

CHICAGO*

325 North Wells Street, Suite 210
Chicago, IL 60654

Printed in Canada 02/2019

NEW YORK*

1140 Broadway, Suite 307
New York, NY 10001

*By appointment only

TO VIEW OUR ENTIRE FABRIC

COLLECTION, VISIT ALLSEATING.COM

T 1 800 563 3502 F 1 800 272 9911